

Calibrationservice

	Temperature	Humidity	Pressure
ISO 9001	Standard for temperature probes and transmitters incl. 3 calibration points 0 °C, 45 °C, 90 °C at room temperature	Standard for humidity probes incl. 3 calibration points 20 % RH, 50 % RH, 80 % RH at room temperature	Standard for pressure measuring transducers incl. 5 calibration points rising and falling -1...150 bar relative, 0...150 bar absolute
	Basic charge* Calibration points:	Additional humidity calibration points: 5...95 % RH	Standard for pressure measuring incl. 10 calibration points rising and falling -1...150 bar relative, 0...150 bar absolute
	Temperature range 1: -30...+100 °C	Standard for humidity reference cell	
	Temperature range 2: +101...+1000 °C		
	Temperature range 3: -60...-30 °C and +1000...+1600 °C		
Standard for temperature measuring devices incl. 10 calibration points			
DAkKS	Standard for temperature probes and transmitters incl. 3 calibration points 0 °C, 45 °C, 90 °C at room temperature	Standard for humidity probes incl. 3 calibration points 20 % RH, 50 % RH, 80 % RH at room temperature	
	Basic charge* Calibration points:	Additional humidity calibration points: 10...90 % RH	
	Temperature range 1: -30...+100 °C		
Temperature range 2: +101...+550 °C			

*at least 3 calibration points are recommended